QUICK START GUIDE

Lotus Diagnostics

OBD Wi-Fi diagnostic interface - initial connection and daily use

CONNECT | OPEN | DIAGNOSE

Connection details

Parameter	Setting
Wi-Fi network	Lotus Diagnostics
Default password	password
Web address	http://10.1.1.1

Initial setup

1. **Power the device.** Plug the diagnostic interface into the vehicle's OBD port.
2. **Open the Wi-Fi settings.** On your mobile phone, search for the network named “Lotus Diagnostics”.
3. **Connect to the device.** Select the “Lotus Diagnostics” Wi-Fi network.
4. **Enter the password.** When prompted, enter “password”.
5. **Open the diagnostic page.** Launch a web browser and enter http://10.1.1.1 in the address bar. If your phone reports that the network has no internet access, confirm that you want to remain connected.
6. **Create a shortcut.** Add the diagnostic page to your phone's Home Screen for faster access.

Daily use

7. **Reconnect via Wi-Fi.** Before each use, connect your phone to the “Lotus Diagnostics” network, then open the Home Screen shortcut created during setup.
8. **Refresh if necessary.** If the page does not load immediately, wait a few seconds and use the browser's reload function.

Important: The diagnostic interface creates a local Wi-Fi connection and does not provide internet access. Keep the phone connected to “Lotus Diagnostics” while using the web interface.